

Zip Tudor



Zip Tudor 5 10 ltr under-sink open outlet water heater for single point of use. Externally adjustable temperature control, with frost protection.

MODEL	ENERGY EFFICIENCY CLASS (ERP)	DIMENSIONS W X D X H	NOMINAL POWER RATING KW	RE-HEAT TIME 10-65oc (HH:MM)	CAPACITY (LITRES)
T5UB10	A	310mm x 265mm x 471mm	2 kW @ 230V AC	0:20	9.9

Features and benefits

- Vented water heater for single point of use.
- Externally adjustable temperature control.
- Manually resettable cut out.
- Choice of 5 and 10 litre capacities.

Safety features

- Vented non pressurised system.
- Pressure and temperature relief valve supplied.
- Heater protected against freezing while power is switched on.
- Manually resettable over temperature safety cut-out.

Product detail

Specification type

Product code	T5UB10
Product name	Tudor 5 10ltr under-sink water heater
Energy Efficiency Class	A
WRAS Approval	No

Capacity, weights & dimensions

Capacity (Litres)	9.9 L
Unit dimensions (W x D x H) mm	310 x 265 x 471

Electrical

Nominal power rating	2 kW @ 230V AC
Nominal power supply	230V
Nominal rated current	8.7 amps
IP rating	24

Plumbing

Wholesome water supply	Yes
Wholesome connection size	1/2BSP



The Zip Tudor must be installed in accordance with the installation instructions and all current legislation, codes of practice and regulations governing the installation of unvented hot water cylinders in force at the time of installation. The appliance must be permanently connected to the supply through an isolating switch with a contact separation of at least 3mm in all poles and be protected by a suitably rated RCD to protect the appliance, an MCB (miniature circuit breaker) or fuse must be fitted with a rating suitable for the nominal current of the appliance.