

Zip Varipoint



Varipoint 2 15ltr over-sink unvented water heater for single or multiple outlets. Heavy gauge copper inner container tested to 16 bar, supplied with temperature and pressure relief valve.



MODEL	ENERGY EFFICIENCY CLASS (ERP)	DIMENSIONS W X D X H	NOMINAL POWER RATING KW	RE-HEAT TIME 10-65oc (HH:MM)	CAPACITY (LITRES)
VP153	A	300mm x 285mm x 452mm	2.2 kW @ 230V AC	0:17	15

Features and benefits

- Heavy gauge copper inner container tested to 16 bar.
- Does not require an anode. Supplied with temperature and pressure relief valve.
- External temperature control with frost protection setting.
- Element 'On' neon indicator.

Safety features

- Manually resettable over temperature cut-out.
- Pressure and temperature relief valve supplied.
- Expansion relief valve supplied, set at 6 bar.
- Frost protection setting.

Product detail

Specification type

Product code	VP153
Product name	Varipoint 2 15ltr over-sink unvented water heater
Energy Efficiency Class	A
WRAS Approval	No

Capacity, weights & dimensions

Capacity (Litres)	15 L
Unit dimensions (W x D x H) mm	300 x 285 x 452

Electrical

Nominal power rating	2.2 kW @ 230V AC
Nominal power supply	230V
Nominal rated current	9.6 amps
IP rating	24

Plumbing

Wholesome water supply	Yes
Wholesome connection size	1/2BSP



The Zip Varipoint must be installed in accordance with the installation instructions and all current legislation, codes of practice and regulations governing the installation of unvented hot water cylinders in force at the time of installation. The appliance must be permanently connected to the supply through an isolating switch with a contact separation of at least 3mm in all poles and be protected by a suitably rated RCD to protect the appliance, an MCB (miniature circuit breaker) or fuse must be fitted with a rating suitable for the nominal current of the appliance.

