












Comfort EVO


Comfort EVO 1 Dual Output CCT Downlight White Code: ACOM1/1

| Category | Downlights |
|---------------|---|
| Application | Ancillary, Commercial, Education, Healthcare, |
| | Hospitality, Retail |
| Specification | Performance |









PRODUCT FEATURES

- Economic high performance CCT selectable IP44 downlight suitable for commercial and healthcare applications
- Deep cut-off angle for glare control and comfort
- $\bullet\,$ Downlight design allows installation into existing hole cut-outs of 210mm
- Polycarbonate housing with unique thermal management for durability and optimum lifespan

| GENERAL INFORMATION | | |
|-------------------------|-------------------------|--|
| Wattage | 7W - 13W | |
| Lumens Delivered | 1000lm - 1800lm (4000K) | |
| Lm/W | 130lm/W (4000K) | |
| Beam Angle | 80 | |
| CRI | 80 | |
| CCT | 3000/4000K | |
| Input | 220/240V | |
| Operating Temp | -20°C - 25°C | |
| SDCM | 3 | |
| UGR | 23 | |
| Cut-Out Size | 210mm | |
| Energy efficiency class | F | |

| TECHNICAL INFORMATION | | |
|--------------------------------|-----------------|--|
| Light Source | LED | |
| Colour / Finish | White | |
| IP Rating | IP44 | |
| Class Protection | 2 | |
| Internal / External | Internal | |
| Surface / Recessed / Suspended | Recessed | |
| Lumen Depreciation L70 B50 | L70 B50 60,000h | |
| Warranty (Years) | 5 | |
| CE Mark | Yes | |
| Height | 62 mm | |

www.ansell-lighting.com Warrington: +44 (0) 1942 433333 Belfast: +44 (0) 2890 773750