PHILIPS Lighting



MASTER Ultra Efficient LED bulb

MAS LEDBulbND5.2-75W E27 830A70 CLG UE

This is the most efficient LED bulb from Philips brand. 210lm/W helps to concrete the company statement of sustainability. 50000 hour lifetime helps to extend the replacement cycle to reduce the waste. This is not only a high SPEC product, but also keeps the light quality of Philips brand

Product data

General information	
Cap base	E27 [E27]
Nominal lifetime	50,000 h
Switching Cycle	50,000
Lighting Technology	LED
Flux measurement reference	Sphere
Light technical	
Colour Code	830 [CCT of 3000K]
Luminous Flux	1,095 lm
Colour designation	White (WH)
Correlated Colour Temperature	3000 K
Luminous Efficacy (rated) (Nom)	210 lm/W
Colour consistency	<6
Colour rendering index (CRI)	80
LLMF at end of nominal lifetime (nom.)	70 %
Operating and electrical	

Line Frequency 50) to 60 Hz
Input frequency 50) to 60 Hz

Power Consumption	5.2 W
Lamp current (nom.)	60 mA
Wattage equivalent	75 W
Starting time (nom.)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.4
Voltage (nom.)	220-240 V
Temperature	
T-Case maximum (nom.)	70 °C
Controls and dimming	
Dimmable	No
Mechanical and housing	
Lamp Finish	Clear
Bulb shape	A70 [A 70 mm]
Approval and application	
Energy Efficiency Class	A

A ↑ G


A

MASTER Ultra Efficient LED bulb

Energy consumption kWh/1,000 hours	6 kWh
EPREL registration number	1370034
CE mark	Yes
EU RoHS compliant	Yes
Product data	
Full EOC	871951443587200
Order product name	MAS LEDBulbND5.2-75W E27 830A70 CLG UE


Order code	43587200
SAP numerator - quantity per pack	1
Numerator – packs per outer box	10
Material number (12NC)	929003480402
Full product name	MAS LEDBulbND5.2-75W E27 830A70 CLG UE
EAN/UPC - Case	8719514435889

Dimensional drawing




Product	D	с
MAS LEDBulbND5.2-75W E27 830A70 CLG UE	70 mm	127 mm

Photometric data



Light Distribution Diagram - MAS LEDBulbND5.2-75W E27 830A70 CLG UE




Spectral Power Distribution Colour - MAS LEDBulbND5.2-75W E27 830A70 CLG UE

		1 × 9299034864 5.2W
		1 - 1015 -
	Variation Ages	
Normal March Street		

General uniform lighting - MAS LEDBulbND5.2-75W E27 830A70 CLG UE

MASTER Ultra Efficient LED bulb

Lifetime



Life Expectancy Diagram - MAS LEDBulbND5.2-75W E27 830A70 CLG UE

80 90 80 70 60 50 0 1000 2000 3000 4000 5000 60000 Burning hours

Lumen Maintenance Diagram - MAS LEDBulbND5.2-75W E27 830A70 CLG UE



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.