



WRSS81BSW



13A 1 Gang Double Pole Switched Socket Brushed Steel White Insert

Technical characteristics

Architecture

Fixing mode	surface-mounting
-------------	------------------

Functions

Overvoltage protection	No
------------------------	----

Configuration

Number of modules	0
-------------------	---

Main electrical features

Nominal voltage	250 V AC
Rated current	13 A

Electric current

Rated current	13 A
---------------	------

Dimensions

Height	86 mm
Width	86 mm

Cover, door

Cover	Full cover plate
-------	------------------

Power supply

Special power supply	No special power supply
----------------------	-------------------------

Materials

Colour of design line	grey
Colour independent of design lines	Grey
Colour	grey
Material	Steel
Type of surface treatment	Epoxy

Installation, mounting

Fixing type	With screws
Installation mode	for surface-mounted housing,for surface mounting

Connection

Type of connection	screw
--------------------	-------

Cable

Wiring	with earth connection
--------	-----------------------

Scope of delivery	
Component	with 2 fixing screws M3.5 x 20 mm and M3.5 x 30 mm each
Equipment	
Number of socket outlets switchable	1
Use	
Differentiation characteristic 3 - Sales	with screw terminals
Safety	
IK protection code against mechanical impacts	sonstige
Protection index IP	IP20
Protection	Enhanced contact protection