PBG - HAMMER PLUG (SCREW INCLUDED)

Description:

Quick and easy to use, an all metal hammerin plug for light duty fixing to plasterboard.

No drilling required

Screw:

4.0 x 30 Cross Recess No2 Screws Included

Features:

- Zinc plated and yellow passivated, to enhance corrosion resistance.
- Steel material offers improved fire resistance compared to plastic or nylon fixings.
- Does not rotate on screwing.
- Serrated point for easy hammering and rapid insertion.



PBG

OTHER ADDITIONAL INFORMATION

Technical Data

Substrate	Plasterboard 12.5 Thickness	
Screw Size (mm)	4.0 x 30	
Plug Size (mm)	11 x 30	
Rec. Tensile Load (kN)	0.10	
Max Rec. Load (kg)	10	

Screw Diameter



HAMMER METAL PLUIG INTO PLASTERBOARD


PLUG





INSERT SCREW
THROUGH
FIXTURE AND
INTO METAL PLUG.
TIGHTEN SCREW
UNTIL SECURE.

Installation Data

Code	^t fix(mm)	DK (mm)	Screw L (mm)	D (mm)	Plug L (mm)
PBG	6	7.5	30	4.0	30







pelica Ltd 2021. This document is provided to the public for information purposes only and is subjected to change without notice. Deliga Ltd make no promise of the document keeping the information contained within