




**Product Description:** InterLED<sup>CS™</sup> 40W Colour Switchable 1500mm Batten


Suitable for a range of commercial applications, the new InterLED<sup>CS™</sup> has a colour switch to simply select between 3000K, 4000K and 6500K. Opal polycarbonate diffuser ensures uniform light distribution. Available in a choice of white or black finish, with an emergency self test option.

SKU Code	Wattage	Colour	Lumens	Beam Angle	Finish Colour	SKU Type
AU-LN1540CSBLK	40	3000K	4280	110	Black	Non Dimmable
AU-LN1540CSBLK	40	4000K	4360	110	Black	Non Dimmable
AU-LN1540CSBLK	40	6500K	4330	110	Black	Non Dimmable
AU-LN1540CSEMBLK	40	3000K	4280	110	Black	Emergency Self-Test
AU-LN1540CSEMBLK	40	4000K	4360	110	Black	Emergency Self-Test
AU-LN1540CSEMBLK	40	6500K	4330	110	Black	Emergency Self-Test
AU-LN1540CSEMW	40	3000K	4280	110	White	Emergency Self-Test
AU-LN1540CSEMW	40	4000K	4360	110	White	Emergency Self-Test
AU-LN1540CSEMW	40	6500K	4330	110	White	Emergency Self-Test
AU-LN1540CSW	40	3000K	4280	110	White	Non Dimmable
AU-LN1540CSW	40	4000K	4360	110	White	Non Dimmable
AU-LN1540CSW	40	6500K	4330	110	White	Non Dimmable

## Line Drawing




## Polar Curve



## Colour



Black



White

## Feature & Benefits

- Colour switchable between 3000K, 4000K & 6500K
- Supplied with 1.5 metre suspension cable & surface mount brackets
- Interconnecting connector supplied
- Can be surface mounted or suspended
- PLEASE NOTE: Product cannot be surface mounted in continuous lengths
- Emergency self test option
- 5 Year Warranty
- 3 year onsite warranty (registration required) \*Terms and conditions apply

## Product Specs:

Input Frequency	50/60HZ	IP Rating	IP20
Lifetime L70 (hrs)	50000hrs	Width (mm)	59
Length (mm)	1500	Height (mm)	70
Product Type	Linears	Operating Temp. (Min) °C	-20°C
Operating Temp. (Max) °C	45°C		

## Compliance & Approvals:



## Warranty:

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.