



KYROS

ELECTRIC TOWEL RAIL WITH THERMAL FLUID

- High-quality ST12 steel body
- Optimum Flux tech: glycol/water high heat transfer thermal fluid
- Wall-mounted with easy installation: includes wall brackets, template & manual
- TFT screen and mechanical keypad
- 24/7 programming with 4 editable pre-installed heating programs
- Compatible with Rointe AIR or BASIC remote controls (sold separately)
- Energy-saving functions: Open Windows, User mode
- Boost function: 15, 30, 60, or 120 minutes at maximum power
- Works with renewable energy sources like solar/PV for sustainable heating
- Guarantee: 10 years body | 3 years electronics



MODEL		KTi030SE*3	KTi050SE*3	KTi075SE*3	KTi100SE*3
TECHNICAL CHARACTERISTICS					
Number of tubes		8	12	16	18
Nominal Power (W)	White	300	500	750	1,000
	Chrome	300	300	500	750
Voltage (V)		220-240	220-240	220-240	220-240
Frequency (Hz)		50	50	50	50
Current (A)	White	1.3	2.2	3.3	4.4
	Chrome	1.3	1.3	2.2	3.3
Finishes		White RAL 9016 / Chrome			
DIMENSIONS					
Height (mm)		900	1,300	1,700	1,900
Width (mm)		500	500	500	500
Depth (mm)		30	30	30	30
Installed Depth (mm)		85	85	85	85
Weight (kg)		9.4	11.8	17.4	19.0
Heats Room Size (m²)		up to 3	up to 5	up to 7.5	up to 10
DIAGRAM					
					
MATERIALS					
Body		Steel ST12			
Control Panel / End Casing		Fire-proof PC/ABS (non yellowing)			
Interior		High heat transfer thermal fluid			
Heating Technology		Optimum Flux			
ELECTRONICS					
Battery		3V			
Electronic Components		SMD			
Energy Control Element		Relay			
Temperature Sensor		NTC High Precision ± 0.1°C			
Cable Length		1.4 m			
Plug		Not included			

KYROS

ELECTRIC TOWEL RAIL WITH THERMAL FLUID

MODEL	KT1030SE*3	KT1050SE*3	KT1075SE*3	KT1100SE*3
SAFETY				
Safety Thermostat & Overheat Detection			✓	
IP Rating			IP44	
Protection Grade			Class II	
TEMPERATURE				
Manual Adjust Temperature			7 to 30°C	
Temperature modes			Off, Anti-Frost, Eco, Comfort	
Anti-Frost Temperature			7°C	
Eco Range Temperature			7.5 to 18.5°C	
Comfort Range Temperature			19 to 30°C	
Ambient Temperature Stability			-	
ENERGY SAVING TECHNOLOGIES & FUNCTIONS				
Energy Control Technology			-	
Programming			24/7	
Preset Heating Programs			✓	
Adaptive Start			-	
Open Windows			✓	
User mode			✓	
Hotel mode			-	
Pilot Wire			Only when specifically ordered	
Programming modes			Manual/Automatic	
Consumption Indicator			✓	
CONTROLS & INTERFACE				
Operation Via Rointe Heating App			-	
Operation Via Remote Control			✓	
Operation Via Control Panel			✓	
Screen			1.77" TFT	
Interactive Menus			✓	
Control Panel Lock			Via control panel	
Remote Control Lock			Via Rointe AIR or BASIC remote control	
Keypad			Mechanical	
WIFI CONTROL & TECHNOLOGIES				
Built-In WiFi (2.4 GHz)			-	
WiFi Direct ¹			-	
Rointe Heating App Control			-	
Rointe Heating App Platforms			-	
Works with Amazon Alexa & Google Assistant			-	
Control by Geolocation			-	
True Real Power Consumption meter			-	
Cost & Consumption control			-	
Customisable Screen Colour			-	
Comfort Index ²			-	
AIH System ²			-	
INSTALLATION				
Mounting			Wall	
Direction			Vertical	
Supplied With			Cable, Installation Kit (template, brackets, screws), User Manual	
PACKAGING INFORMATION				
Height (mm)	1,000	1,350	1,750	2,000
Width (mm)	550	550	550	550
Depth (mm)	100	100	100	100
Gross Weight (kg)	11.0	14.0	20.0	22.0

KYROS

ELECTRIC TOWEL RAIL WITH THERMAL FLUID

MODEL	KT1030SE*3	KT1050SE*3	KT1075SE*3	KT1100SE*3
GUARANTEE				
Steel Body Guarantee	10 years			
Electronic Components Guarantee	3 years			
APPROVALS, CERTIFICATIONS & CONFORMITIES				
CE	✓			
UKCA	✓			
NF	-			
RoHS	✓			
ERP Ready - LOT20	✓			
ETIM Class	EC003624			
COMPATIBLE ACCESSORIES				
Racks	-			
Hooks/Hangers	-			
Remote Control (Infrared)	✓			

1) Compatible with 2.4 GHz. No need for gateways or other connections. 2) Available from Q3/Q4 2023.

Available
Finishes/Colours



White RAL 9016



Chrome

