





Floodlights

Performance








## **Calinor EVO**

Calinor EVO Floodlight PIR Cool White 50W Black

Code: ACAE50/1/CW/B/PIR








Category

**Application** 

Specification



Commercial, Industrial, Outdoor, Retail

## PRODUCT FEATURES

- Compact, slim and robust designed LED floodlight suitable for residential and commercial applications
- Toughened microprism glass for visual comfort, uniformity and durability
- Pre-wired with 1 metre of rubber insulated cable for ease of installation and easy integration with Floodbox accessory
- Polycarbonate spike accessory allowing installation into lawn and garden applications
- Polycarbonate front trim provides excellent corrosion resistance
- Bracket design allows installation without removing mounting bracket
- Breather gland acts to minimise risk of water ingress
- PIR versions complete with manual override facility

GENERAL INFORMATION		
Wattage	50W	
Lumens Delivered	5400lm	
Lm/W	111lm/w	
Beam Angle	100	
CRI	80	
CCT	4000K	
Input	220/240V	
Operating Temp	-15°C - 40°C	
SDCM	6	
Energy efficiency class	D	

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	Black	
IP Rating	IP65	
Class Protection	1	
Internal / External	External	
Surface / Recessed / Suspended	Wall	
Lumen Depreciation	L80 69,000h	
Warranty (Years)	5	
CE Mark	Yes	
Height	246 mm	