



@ansell\_lighting



anselllighting



Ansell Lighting






ansell\_lighting

# Pace UGR<19 600x600

Pace Backlit 600x600 Panel UGR<19 Warm White

Code: APAC1/60/1/WW

|               |                                                                  |
|---------------|------------------------------------------------------------------|
| Category      | Commercial Panels                                                |
| Application   | Ancillary, Commercial, Education, Healthcare, Industrial, Retail |
| Specification | Performance                                                      |



## PRODUCT FEATURES

- Backlit LED panel suitable for education, commercial and ancillary area applications
- UGR<19 (unified glare rating) compliant luminaire assisting to eliminate glare for visual comfort
- Dimmable and OCTO options available
- Switch Dim, DALI and 0-10V dimming capability using the multi dimmable driver accessories ADDIM/30/MC
- Slimline design allows for installation into shallow ceiling voids
- Cool white, warm white and daylight options
- TPA as standard
- Self-Test Panel Pod and Sensor Pod compatible

## GENERAL INFORMATION

|                  |              |
|------------------|--------------|
| Wattage          | 28W          |
| Lumens Delivered | 3200lm       |
| Lm/W             | 115lm/W      |
| Beam Angle       | 90           |
| CRI              | 80           |
| CCT              | 3000K        |
| Input            | 220/240V     |
| Operating Temp   | -20°C - 40°C |
| SDCM             | 3            |
| UGR              | 18           |
| Cut-Out Size     | 585x585mm    |

## TECHNICAL INFORMATION

|                                |                              |
|--------------------------------|------------------------------|
| Light Source                   | LED                          |
| Colour / Finish                | White                        |
| IP Rating                      | IP40                         |
| Class Protection               | 2                            |
| Internal / External            | Internal                     |
| Surface / Recessed / Suspended | Ceiling, Recessed, Suspended |
| Lumen Depreciation             | L80 60,000h                  |
| Warranty (Years)               | 5                            |
| CE Mark                        | Yes                          |
| Height                         | 32 mm                        |

