





Floodlights

Performance








Aztec Coastal Asymmetric

Aztec Coastal Asymmetrical Floodlight 50W

Code: AAZCLED50/ASY



Category

Application

Specification



Ancillary, Commercial, Education, Healthcare, Hospitality, Industrial, Outdoor, Retail

PRODUCT FEATURES

- High performance die-cast marine grade aluminium LED floodlight suitable for industrial and coastal applications
- Marine grade construction ideal for coastal and adverse weather, swimming pool and chemical plant applications
- Pre-installed breathable gland prevents internal moisture accumulation
- Concentrated saline 3,000 hour salt spray test to EN ISO 9227

- 304L stainless steel mounting bracket and fixings
- High output, high efficiency asymmetric lens technology for anti-light pollution
- $\bullet\,$ Pre-wired with 1.5 metre of rubber insulated cable for ease of installation
- High purity aluminium construction, surface electrophoresis and corrosion-proof treatment

GENERAL INFORMATION		
Wattage	50W	
Lumens Delivered	6800lm	
Lm/W	136lm/W	
Beam Angle	60/120	
CRI	70	
CCT	5000K	
Input	220/240V	
Operating Temp	-30°C - 50°C	
SDCM	5	

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	Aluminium	
IP Rating	IP66	
Class Protection	1	
Internal / External	External	
Surface / Recessed / Suspended	Pole, Wall	
Lumen Depreciation	L80 54,000h	
Warranty (Years)	5	
CE Mark	Yes	
Height	267 mm	

A

www.ansell-lighting.com Warrington: +44 (0) 1942 433333 Belfast: +44 (0) 2890 773750