

# Zip Hydroboil Plus

## Instant on-wall boiling water



With all the benefits of the HydroBoil, the HydroBoil Plus is our most technologically advanced model and is designed to cut energy consumption. It features energy-saving Power-Pulse<sup>®</sup> technology, inactivity and low light sleep modes and is equipped with a cool-touch two-way safety tap and safety lock.



| MODEL  | TANK SIZE<br>(litres) | HEAT UP TIME<br>(INLET 15°C) | HEAT UP TIME<br>(INLET 10°C) | NOMINAL POWER<br>RATING KW | DIMENSIONS<br>W X D X H | FILLED<br>WEIGHT |
|--------|-----------------------|------------------------------|------------------------------|----------------------------|-------------------------|------------------|
| 403562 | 3                     | 16mins                       | 17mins                       | 1.4 kW @ 230V AC           | 300mm x 183mm x 439mm   | 12.5kg           |

## Features and benefits

### Convenience

The Hydroboil range delivers reliable boiling water instantly, saving time and helping to increase workplace productivity.

### Space saving

Wall-mounted units save much-needed counter-top and under-counter space.

### Easy and safe to use

Simple controls and a range of safety features give you complete peace of mind.

### Energy efficient

Steam-Heat-Boost technology saves energy by recycling steam to pre-heat incoming cold water – making boiling quicker and less costly.

### Wide range

With capacities ranging from 1.5 to 40 litres, there is a model for every situation.

## Product detail

### Specification type

|                       |   |
|-----------------------|---|
| Product code          | 403562 (HP003)  |
| Product name          | HydroBoil Plus HP003 3ltr Instant on-wall boiling water heater in white |
| Case material         | Corrosion Resistant White Enamelled Steel                               |
| Instant boiling water | Twin chamber  |
| Control               | Electronic  |
| Service Access Port   | Top and bottom  |

### Capacity, weights & dimensions

|                            |                       |
|----------------------------|-----------------------|
| Capacity                   | 3ltrs                 |
| Unit dimension (W x D x H) | 300mm x 183mm x 439mm |
| Product weight             | 12.5kg                |

### Plumbing

|  |   |
|--|---|
| Wholesome cold water inlet supply required | Yes   |
| Supply pressure range                      | 0.07 MPa (0.7bar) - 0.5 (5bar)                    |
| Inlet pipe                                 | 1/2" BSP  |
| Vent pipe                                  | 15mm  |
| Vent discharge                             | Visible tundish or drainage board                 |
| Installation                               | Must comply with current water supply regulations |

The minimum water pressure will vary if a limescale filter is installed. Please contact us to discuss your requirements.

### Electrical

|                                 |   |
|---------------------------------|---|
| Nominal power rating kw         | 1.4 kW @ 230V AC                                      |
| Power supply 1.5L to 25L models | 1 x 13A double pole isolation switch or socket outlet |
| Installation                    | Must comply with current IEE regulations              |

### Warranty

|   |   |
|---|---|
| 2 Year on-site parts and labour on site | Terms and conditions apply (visit website for more information) |
|---|---|

