




**Product Description:**

**Spryte™ 10W Fixed Integrated IP44 Dimmable Downlight**


Spryte™ LED downlight range is the ideal energy efficient non-fire rated solution for new build or retrofit installations. Fitted with the edge-to-edge, multifaceted, 60° wide beam EnFiniti™ lens, these downlights allow for high light output and low glare while still providing a sparkling halogen like optical appearance in a compact sized fitting.

| SKU Code      | Wattage | Colour | Lumens | Lumens/Watt | Beam Angle | Finish Colour | SKU Type       |
|---------------|---------|--------|--------|-------------|------------|---------------|----------------|
| EN-DDL1019/30 | 10      | 3000   | 1020   | 102         | 60         | Matt White    | Triac Dimmable |
| EN-DDL1019/40 | 10      | 4000   | 1100   | 110         | 60         | Matt White    | Triac Dimmable |

**Line Drawing**



**Polar Curve**



**Colour**



Matt White

## Feature & Benefits

- Energy efficient LED downlight for new build or halogen and reflector lamp retrofit applications
- EnFiniti™ edge-to-edge multifaceted polycarbonate lens creates low glare and halogen like appearance
- Integrated driver for easy installation and low ceiling voids
- Supplied with interchangeable round & square white bezels
- Triac dimmable
- Pre-wired with 500mm 2 core cable
- Fixed & adjustable versions IP44 rated
- 1.5kV surge protection

## Product Specs:

|                          |             |                          |       |
|--------------------------|-------------|--------------------------|-------|
| Input Voltage            | 220~240V AC | Input Frequency          | /50HZ |
| Power Factor             | 0.5         | IP Rating                | IP44  |
| Lifetime L70 (hrs)       | 25000hrs    | IK Rating                | IK03  |
| Lamp Base                | None        | Overall Diameter (mm)    | 105   |
| Weight (Kg)              | 0.229       | Height (mm)              | 57    |
| Product Type             | Downlights  | Cutout Diameter (mm)     | 90-90 |
| Operating Temp. (Min) °C | -20°C       | Operating Temp. (Max) °C | 40°C  |

## Compliance & Approvals:



## Warranty:

This product has a warranty period of 3 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.