



Product Code: FS032SS

Luckinslive 389093440

Description: 13A 2 Gang Floor Socket Outlet



General Information

Dimensions (mm)	146 (W) x 93 (D) x 5 (H)	
Plate Fixing Centres - Horizontal (mm)	120.6	
Finish	Stainless Steel	
Materials	Plate & Lid: Stainless Steel	Insert: Urea
	Internal Busbars: Brass	Terminals: Brass
	Terminal Screws: Steel and Yellow Passivated	Earth Bar: Mild Steel
Anti Microbial Certified	Yes	
Operating Voltage (AC)	250	Frequency (Hz) 50
Resistive Load Rating (A)	13	
Termination Type	Screw	
Terminal Size (mm)	Ø5	Terminal Torque Value (Nm) 2
Terminal Capacity - Solid (mm²)	3 x 2.5 or 2 x 4	
Switched	No	
Twin Earth Terminals	Yes	
Minimum Back Box Depth (mm)	35	
Ingress Protection	IP20	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	10	

Standards BS 1363-2

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.



Catalogue



Range



DoC



Installation

