

Product Code: VPAB022BK

Technical Specification



Description: 20A Double Pole Plate Switch With Optional Flex Outlet







Insert, Switch & Rear Housing: Urea

Gasket: Nylon

Terminal Screws: Steel & Yellow Passivated

Internal Busbars: Formed Pressed Brass

General Information

Plate Dimensions (mm) 88 (W) x 88 (H) x 8 (D)

Dimensions With Gasket (mm) 91 (W) x 91 (H) x 9 (D)

Plate Fixing Centres - Horizontal (mm) 60.3

> Style Victorian

Finish Antique Brass

Insert Colour Black Gasket Colour Black

> Materials Front Plate: Stainless Steel

> > Terminals: Brass Contacts: Silver "on-lay" Copper / Brass

Earth Strap: Mild Steel

Anti Microbial Certified

Operating Voltage (AC) 250 Frequency (Hz) 50

Resistive Load Rating (A) 20 Termination Type Screw

> Terminal Torque Value (Nm) 1.8 Terminal Size (mm) Ø5

Terminal Capacity - Solid (mm²) 3 x 2.5 Double Pole Switch Yes Twin Earth Terminals Yes

Flex Outlet Available Yes

Flex Outlet Location Front of Plate Flex Outlet Dimension (mm) Ø10

Minimum Back Box Depth (mm) 25

Ingress Protection IP20 Operational Temperature (°C) -5 to +40 Warranty (Years) 20

BS EN 60669-1 Standards

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.









Scolmore House, Mariner, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7UL United Kingdom **T:** +44 (0)1827 63454 | **F:** +44 (0)1827 63362

E: sales@scolmore.com | W: scolmore.com