

Product Code: VPAB035BK

Technical Specification

Luckinslive 389108296







General Information

Plate Dimensions (mm) 88 (W) x 88 (H) x 8 (D)

Dimensions With Gasket (mm) 91 (W) x 91 (H) x 9 (D)

Plate Fixing Centres - Horizontal (mm) 60.3

> Style Victorian

Finish Antique Brass Insert Colour Black

Gasket Colour Black

> Materials Front Plate: Stainless Steel

> > Terminals: Brass Contacts: Silver "on-lay" Copper / Brass

Earth Strap: Mild Steel

Anti Microbial Certified

Operating Voltage (AC) 250

Resistive Load Rating (A) 13 Termination Type Screw

Terminal Size (mm) Ø5

Terminal Capacity - Solid (mm²) 3 x 2.5 or 2 x 4

Double Pole Switch Yes Twin Earth Terminals No

Minimum Back Box Depth (mm)

Ingress Protection

Operational Temperature (°C) -5 to +40

Warranty (Years)

Standards BS 1363-2

Insert, Switch & Rear Housing: Urea Terminal Screws: Steel & Yellow Passivated

Internal Busbars: Formed Pressed Brass

Gasket: Nylon

Frequency (Hz) 50

Terminal Torque Value (Nm) 2

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.







UK Design Registration: 3015621





T: +44 (0)1827 63454 | **F:** +44 (0)1827 63362 E: sales@scolmore.com | W: scolmore.com