


Technical Specification





Luckinslive 389108351







General Information



Plate Dimensions (mm)	88 (W) × 88 (H) × 8 (D)			
Dimensions With Gasket (mm)	91 (W) \times 91 (H) \times 9 (D)			
Plate Fixing Centres - Horizontal (mm)	60.3			
Style	Victorian			
Finish	Antique Brass			
Insert Colour	Black			
Gasket Colour	Black			
Materials	Front Plate: Stainless Steel		Insert, Switch, Fuse [Drawer & Housing: Urea
	Terminals: Brass		Terminal Screws: Ste	el & Yellow Passivated
	Contacts: Silver "on-lay" Copper / Bra	SS	Internal Busbars: For	med Pressed Brass
	Earth Strap: Mild Steel		Gasket: Nylon	
Anti Microbial Certified	No			
Operating Voltage (AC)	250		Frequency (Hz)	50
Resistive Load Rating (A)	13			
Fuse Fitted Type	Plug Top Cartridge Fuse			
Termination Type	Screw			
Terminal Size (mm)	Ø5	Termina	Il Torque Value (Nm)	2
Terminal Capacity - Solid (mm²)	3 x 2.5 or 2 x 4			
Switched	Yes			
Double Pole Switch	Yes			
Twin Earth Terminals	Yes			
Product Marking	Fused			
Flex Outlet Available	Yes			
Flex Outlet Location	Front of Plate	Flex Out	let Dimension (mm)	Ø10
Minimum Back Box Depth (mm)	25			
Ingress Protection	IP20			
Operational Temperature (°C)	-5 to +40			
Warranty (Years)	20			
Standards BS 1363-4, BS 13	362			

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Scolmore House, Mariner, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7UL United Kingdom **T:** +44 (0)1827 63454 | **F:** +44 (0)1827 63362 E: sales@scolmore.com | W: scolmore.com









UK Design Registration: 3015621

