

Product Code: VPAB159BK

Description: Twin Isolated Coaxial Outlet

Technical Specification

Luckinslive 389108607





General Information

Plate Dimensions (mm) 88 (W) x 88 (H) x 8 (D)

Dimensions With Gasket (mm) 91 (W) x 91 (H) x 9 (D)

Plate Fixing Centres - Horizontal (mm) 60.3

> Style Victorian

Finish Antique Brass

Insert Colour Black Gasket Colour Black

Materials Front Plate: Stainless Steel Insert: Urea

> Terminals: Brass Earth Plate: Mild Steel

Gasket: Nylon

Anti Microbial Certified No

Termination Type Screw

Isolated Yes

Isolated Comments Enables 1 way signal, reducing signal interference

Non-Isolated No Shielded No

Minimum Back Box Depth (mm) 16 IP20 Ingress Protection

Operational Temperature (°C) Warranty (Years)

Warranty - Electronics (Years) 2

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Isolated socket will filter out any interference, if a 2 way signal is required, i.e. for use with satellite hard wire extensions, then a non-isolated outlet is required.











Scolmore House, Mariner, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7UL United Kingdom **T:** +44 (0)1827 63454 | **F:** +44 (0)1827 63362

E: sales@scolmore.com | W: scolmore.com

UK Design Registration: 3015621