

Product Code: VPAB423

## **Technical Specification**

Luckinslive 389108843

Description: 10AX 3 Gang 2 Way Toggle Plate Switch





Contacts: Silver "on-lay" Copper / Brass

Earth Strap: Mild Steel

## **General Information**

Plate Dimensions (mm) 146 (W) x 88 (H) x 8 (D)

Dimensions With Gasket (mm) 149 (W) x 91 (H) x 9 (D)

Plate Fixing Centres - Horizontal (mm) 120.6

> Style Victorian

Finish Antique Brass

Gasket Colour Black

Switch Finish Antique Brass

> Materials Front Plate: Stainless Steel Switch Front & Nut: Cast Zinc

> > Rear Housing: Nylon Terminals: Brass

Terminal Screws: Steel & Yellow Passivated

Internal Busbars: Formed Pressed Brass

Gasket: Nylon

Anti Microbial Certified Frequency (Hz) 50 Operating Voltage (AC) 250

Inductive Load Rating (AX)

**Load Rating Comments** Suitable for Fluorescent or Inductive Loads

**Termination Type** 

Terminal Torque Value (Nm) 1.2 Terminal Size (mm) 4.9 × 4.1

Terminal Capacity - Solid (mm<sup>2</sup>)  $4 \times 1.5$  or  $2 \times 2.5$ 

Modular Rocker Switches

2 Way Switch

Minimum Back Box Depth (mm)

Ingress Protection IP20

Operational Temperature (°C) -5 to +40 Warranty (Years)

Standards BS EN 60669-1

## Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Intermediate toggle switches modules are available which interchange with the modules fitted. Order MDg125AB for antique brass finish.









Scolmore House, Mariner, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7UL United Kingdom **T:** +44 (0)1827 63454 | **F:** +44 (0)1827 63362 E: sales@scolmore.com | W: scolmore.com