

Product Code: VPAB552BK

Technical Specification

Luckinslive 390052852

Description: 13A Ingot Double Pole Switched Fused Connection Unit With Neon & Optional Flex Outlet





General Information

Plate Dimensions (mm) 88 (W) x 88 (H) x 8 (D)

Dimensions With Gasket (mm) 91 (W) x 91 (H) x 9 (D)

Plate Fixing Centres - Horizontal (mm) 60.3

> Style Victorian

Finish Antique Brass

Insert Colour Black Gasket Colour Black

> Materials Front Plate: Stainless Steel

> > Switch & Fuse Drawer Cover: Stainless Steel

Terminals: Brass

Contacts: Silver "on-lay" Copper / Brass

Earth Strap: Mild Steel

Neon Lens: Polycarbonate Terminal Screws: Steel & Yellow Passivated

Frequency (Hz) 50

Insert & Housing: Urea

Internal Busbars: Formed Pressed Brass

Red

Gasket: Nylon

Anti Microbial Certified

Operating Voltage (AC) 250

Resistive Load Rating (A)

Fuse Fitted Type Plug Top Cartridge Fuse

Termination Type Screw

Terminal Size (mm) Terminal Torque Value (Nm) 2

Terminal Capacity - Solid (mm²) 3 x 2.5 or 2 x 4

> Switched Yes

Double Pole Switch Twin Earth Terminals

> Neon Indicator Yes

Indicator Colour

Product Marking Fused Flex Outlet Available Yes

Flex Outlet Location Front of Plate

Flex Outlet Dimension (mm) Ø10

Minimum Back Box Depth (mm) 25

Ingress Protection IP20 Operational Temperature (°C) -5 to +40

Warranty (Years)

Standards BS 1363-4, BS 1362

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Scolmore House, Mariner, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7UL United Kingdom **T:** +44 (0)1827 63454 | **F:** +44 (0)1827 63362

E: sales@scolmore.com | W: scolmore.com











UK Design Registration: 3015621