

Technical Specification

Luckinslive 389108937

Product Code: VPAB651BK

Description: 13A Double Pole Switched Fused Connection Unit







General Information

Plate Dimensions (mm) 88 (W) x 88 (H) x 8 (D)

Dimensions With Gasket (mm) 91 (W) x 91 (H) x 9 (D)

Plate Fixing Centres - Horizontal (mm) 60.3

> Style Victorian

Finish Antique Brass

Insert Colour Black Gasket Colour Black

> Materials Front Plate: Stainless Steel

> > Terminals: Brass Contacts: Silver "on-lay" Copper / Brass

Earth Strap: Mild Steel

Anti Microbial Certified Operating Voltage (AC) 250

Resistive Load Rating (A)

Fuse Fitted Type Plug Top Cartridge Fuse

Termination Type Screw

Terminal Size (mm)

Terminal Capacity - Solid (mm²) 3 x 2.5 or 2 x 4

Switched

Double Pole Switch Twin Earth Terminals Product Marking Fused

Minimum Back Box Depth (mm) 25

Ingress Protection IP20

Operational Temperature (°C) -5 to +40

Warranty (Years) 20

Standards BS 1363-4, BS 1362 Insert, Switch, Fuse Drawer & Housing: Urea

Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass

Gasket: Nylon

Frequency (Hz) 50

Terminal Torque Value (Nm) 2

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.









Scolmore House, Mariner, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7UL United Kingdom **T:** +44 (0)1827 63454 | **F:** +44 (0)1827 63362 E: sales@scolmore.com | W: scolmore.com