

Product Code: VPAB653BK

## **Technical Specification**

Luckinslive 389108953





Description: 13A Fused Connection Unit With Neon



Gasket: Nylon

Indicator Colour

## **General Information**

Plate Dimensions (mm) 88 (W) x 88 (H) x 8 (D)

Dimensions With Gasket (mm) 91 (W) x 91 (H) x 9 (D)

Plate Fixing Centres - Horizontal (mm) 60.3

> Style Victorian Finish Antique Brass

Insert Colour Black Gasket Colour Black

> Materials Front Plate: Stainless Steel Insert, Fuse Drawer & Housing: Urea

> > Neon Lens: Polycarbonate Terminals: Brass

Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass

Earth Strap: Mild Steel

250 Frequency (Hz) 50

Operating Voltage (AC) Resistive Load Rating (A) 13

Anti Microbial Certified

Fuse Fitted Type Plug Top Cartridge Fuse

**Termination Type** Screw

Terminal Size (mm) Terminal Torque Value (Nm) 2

Terminal Capacity - Solid (mm²) 3 x 2.5 or 2 x 4

Switched

Twin Earth Terminals

Neon Indicator

Product Marking Fused Minimum Back Box Depth (mm) 25

Ingress Protection IP20

Operational Temperature (°C) -5 to +40

> Warranty (Years) 20

**Standards** BS 1363-4, BS 1362

## **Additional Information**

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.









Scolmore House, Mariner, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7UL United Kingdom **T:** +44 (0)1827 63454 | **F:** +44 (0)1827 63362 E: sales@scolmore.com | W: scolmore.com