

ZV900

Automatic Switch Load Controller

Features & Benefits

- Eliminates glow and flicker issues in LED/CFL lamps when used with 2-wire automatic light switches (i.e. Timed, PIR, Photocell automatic switches)
- Under 1W power consumption
- Built-in surge suppression
- No additional cabling to the switch required
- Fits in the ceiling through a 50mm hole
- Specifically designed to operate with Timeguard ZV700, ZV700B, ZV210, ZV215, DS1, ZV810, ST210 and ST810 when used with LED or CFL lighting
- The ZV900 is suitable for other companies 2-wire electronic wall switch products
- IP20 weatherproof rating



Technical Data

Operating Voltage	230V AC
Frequency	50Hz
Installation Type	Surface (In-line)
Earth Class Rating	Class I
Operating Temperature	0°C to 40°C
Ingress Protection Rating	IP20
Standby Consumption	<1W
Switch rating	6A Resistive, 5A Inductive, 3W - 200W CFL, 76W Fluorescent, 200W LED

Data sheet

ZV900

Light / Automatic Light Switches

Cable Entry(s)	Side Entry
----------------	------------

General

Height (mm)	28
Width (mm)	119
Depth (mm)	42
Body Construction	Polycarbonate
Product Colour	White
EAN Number	5012483013434
Guarantee Period	3 Years
Trade Tariff Commodity Code	8536909500

Line Diagrams

