

Product Code: MD018BN-TD

Luckinslive 405858718

Description: 13A/10AX Ingot Double Pole Switch Module



General Information

Dimensions (mm)	25 (W) x 53 (H) x 20 (D)		
Finish	Black Nickel		
Materials	Rocker Switch: Urea		Rear Housing: Nylon
	Switch Cover: Stainless Steel		Terminals: Brass
	Terminal Screws: Steel & Yellow Passivated		Contacts: Silver "on-lay" Copper / Brass
	Internal Busbars: Formed Pressed Brass		
Operating Voltage (AC)	250	Frequency (Hz)	50
Resistive Load Rating (A)	13		
Inductive Load Rating (AX)	10		
Load Rating Comments	Suitable for Fluorescent or Inductive Loads		
Termination Type	Screw		
Terminal Size (mm)	Ø3.5	Terminal Torque Value (Nm)	0.5
Terminal Capacity - Solid (mm²)	4 x 1.5 or 2 x 2.5		
Modular Rocker Switches	Yes		
Double Pole Switch	Yes		
Product Marking	Tumble Dryer		
Minimum Back Box Depth (mm)	16 (25 Flat Plate)		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	20		

Standards BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

