

Technical Specification

Product Code: MM038BK Description: 5A Round Pin Socket Outlet Module

Luckinslive 392589307









Dimensions (mm)	50 (W) x 50 (H) x 27.1 (D)		
Colour	Black		
Materials	Cover & Housing: Polycarbonate	Terminals: Brass	
	Terminal Screws: Steel & Yellow Passivat	ed Internal Busbars: For	med Pressed Brass
Anti Microbial Certified	No		
Operating Voltage (AC)	250	Frequency (Hz)	50
Resistive Load Rating (A)	5		
Termination Type	Screw		
Terminal Size (mm)	Ø5 Te	rminal Torque Value (Nm)	1.2
Terminal Capacity - Solid (mm²)	4 x 1.5 or 3 x 2.5		
Minimum Back Box Depth (mm)	25 (35 Flat Plate)		
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	2		

Standards BS 546

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Scolmore House, Mariner, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7UL United Kingdom T: +44 (0)1827 63454 | F: +44 (0)1827 63362 E: sales@scolmore.com | W: scolmore.com







