

Technical Specification






Apertures

Product Code: MP6o6SCBK





General Information

Plate Dimensions (mm) 250 (W) x 216 (H) x 8 (D)

Dimensions With Gasket (mm) 254 (W) x 220 (H) x 9 (D)

New Media Aperture Dimensions (mm) 75 x 50 (x2)

New Media Module Quantity Accepts Upto 2 Rows of 3 x 25mm x 50mm Modules

Style

Finish Satin Chrome

Insert Colour Black Gasket Colour Black

> Materials Front Plate: Stainless Steel

Insert, Rear Housing & Rocker Switch: Urea Terminals: Brass Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass

Earth Strap: Mild Steel

Anti Microbial Certified

Operating Voltage (AC) 250 Frequency (Hz) 50

Resistive Load Rating (A) 13 **Termination Type** Screw

Terminal Size (mm) Ø5 Terminal Torque Value (Nm) 2.5

Terminal Capacity - Solid (mm²) 3 x 2.5 or 2 x 4

> Double Pole Switch Yes Twin Earth Terminals Yoke Required

Compatible Back Box (mm) MP535 (35) Or MP525 (47)

Ingress Protection IP20 Operational Temperature (°C) -5 to +40 Warranty (Years)

Standards BS 1363-2

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Requires MP525 or MP535 flush back box.

Interchangeable with modules in the New Media Range





