

Technical Specification

Luckinslive 425812459

Product Code: CMA100AG

Р

Description: 115V/230V Dual Voltage Shaver Socket Outlet

General Information			
Plate Dimensions (mm)	86 (W) × 146 (H) × 9.5 (D)		
Plate Fixing Centres - Vertical (mm)	120.6		
Style	Rounded Profile		
Colour	Anthracite Grey		
Materials	Front Plate: Urea	Rear Housing: Urea	
	Terminals: Brass		el & Yellow Passivated
	Contacts: Silver "on-lay" Copper / Brass Earth Strap: Mild Steel	Internal Busbars: For	med Pressed Brass
Anti Microbial Certified	Yes		
		Frequency (Hz)	50/60
Operating Voltage (AC)	220-240	Frequency (HZ)	50700
Load Rating @115V (Va) Load Rating @230V (Va)	20 20		
Thermal Protection Device	20 PTC Resettable Fuse		
Termination Type Terminal Size (mm)	Screw Co. 5		0.5
		rminal Torque Value (Nm)	0.5
Terminal Capacity - Solid (mm²)	2 x 1.5 or 1 x 2.5		
Socket Features	Safety Interlock Shutter		
Twin Earth Terminals	Yes		
Product Marking	Shavers Only, 230V~, 115V~		
Minimum Back Box Depth (mm)	47		
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	25 Warr	ranty - Electronics (Years)	2
Standards BS EN IEC 61558-1, BS EN 61558-2-5			

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

This outlet is not continuously rated and therefore not suitable for use as a permanent charging outlet.

CLICK dual voltage shaver outlets incorporate a double wound isolating transformer rated 20Va at 230V or 115V and meets BS EN 61558-2-5:2010 making it safe for use in bathrooms.

PTC resettable fuses increase resistance as temperature increases due to increased flow. PTC resettable fuses are designed to limit unsafe currents while allowing constant safe current levels, resistance will "reset" automatically when the fault is removed and temperature returns to a safe level.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

All white & grey moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses. All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.

Scolmore House, Mariner, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7UL United Kingdom T: +44 (0)1827 63454 | F: +44 (0)1827 63362 E: sales@scolmore.com | W: scolmore.com

Specification is subject to change without notice. Errors & Omissions excluded.



Page 1 of 1 (20-04-24)







