





Product Description:


MestorCWS™ Colour & Wattage Switchable IP65 Bulkhead


Three colour temperatures and three wattages in one product! Being IP65 rated makes this new MestorCWSTM ideal for outdoor and damp locations. Additionally, this product offers plug and play emergency and microwave sensor packs making the range perfect for the wholesaler to control stock levels and store less products, whilst also being simple for the contractor to convert on site. 54 product combinations in one!

| SKU Code | Wattage | ColorTemp | Lumens | BeamAngle | SKUType | FinishColor |
|-------------|---------|-----------|--------|-----------|--------------|-------------|
| AU-BHE20CWS | 12 | 3000K | 1105 | 120 | Non Dimmable | White |
| AU-BHE20CWS | 12 | 4000K | 1200 | 120 | Non Dimmable | White |
| AU-BHE20CWS | 12 | 6500K | 1200 | 120 | Non Dimmable | White |
| AU-BHE20CWS | 16 | 3000K | 1400 | 120 | Non Dimmable | White |
| AU-BHE20CWS | 16 | 4000K | 1600 | 120 | Non Dimmable | White |
| AU-BHE20CWS | 16 | 6500K | 1600 | 120 | Non Dimmable | White |
| AU-BHE20CWS | 20 | 3000K | 1750 | 120 | Non Dimmable | White |
| AU-BHE20CWS | 20 | 4000K | 1950 | 120 | Non Dimmable | White |
| AU-BHE20CWS | 20 | 6500K | 1950 | 120 | Non Dimmable | White |

Polar Curve

Colour







Feature & Benefits

- Colour switchable between 3000K, 4000K and 6500K
- IP65 rated

- IK10 rated
- -20 +40° ambient operating temperature
- Four conduit entries
- Plug and play emergency, emergency self test and microwave corridor sensing packs available
- 5 Year Warranty

Product Specs:

| Input Voltage | 220~240V AC |
|--------------------------|-------------|
| Power Factor | 0.7 |
| Lifetime L70 (hrs) | 30000hrs |
| Lamp Base | None |
| Weight (Kg) | 0.829 |
| Product Type | Bulkheads |
| Operating Temp. (Max) °C | 40°C |

| Input Frequency | 50/60HZ | |
|--------------------------|---------|--|
| IP Rating | IP65 | |
| IK Rating | IK10 | |
| Overall Diameter (mm) | 320 | |
| Projection (mm) | 80 | |
| Operating Temp. (Min) °C | -20°C | |

Compliance & Approvals:













This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.