

Poly-SlimCS™

Colour Switchable Low Profile Polycarbonate Downlights



- Colour switchable between 3000K/4000K/6500K
- Edge-lit low profile ideal for installations with limited recess space
- Supplied with remote non-dimmable constant current driver

Technical Specifications

- Supply Voltage: 220-240 AC
- Lifespan: L70 40,000hrs
- Operating Temperature: -20°C / 40°C
- Body: Polycarbonate
- Diffuser: Opal Polycarbonate
- Warranty: 3 Years

Cat No.	Type	Watts (W)	Colour Temp. (K)	Lumens (lm)	Lm/W	Beam (°)	Cutout (mm)	Size (mm)	Finish
AU-PLPC06CS	Non Dim	6	3000 / 4000 / 6500	510 - 550	92	120	115	128x 25	White
AU-PLPC09CS	Non Dim	9	3000 / 4000 / 6500	850 - 950	106	120	130	146 x 25	White
AU-PLPC12CS	Non Dim	12	3000 / 4000 / 6500	1200 - 1300	108	120	150	170 x 25	White
AU-PLPC18CS	Non Dim	18	3000 / 4000 / 6500	1850 - 2000	111	120	210	224 x 25	White
AU-PLPC24CS	Non Dim	24	3000 / 4000 / 6500	2500 - 2650	100	120	280	298 x 25	White
AU-EM1EX	3 Hour Maintained Emergency Pack - for Downlights & Panels								
AU-EM1EXST	3 Hour Maintained Self Test Emergency Pack - for Downlights & Panels								
EN-DLEM3	3 Hour Maintained Emergency Pack - for Downlights								