



**AZTEC LED**


- High performance die-cast aluminium LED floodlight suitable for industrial, commercial and coastal applications
- High output, high efficiency asymmetric lens technology for anti-light pollution (asymmetric versions only)
- Marine grade construction ideal for coastal and adverse weather, swimming pool and chemical plant applications
- CCT selectable between 3000K, 4000K and 5000K
- Integral photocell with 2 x lux settings and off options
- Fast fit lever terminals ensure easy and speedy loop-in, loop installation
- 10KV surge protection on 120W to 320W, 6KV surge protection on 20W to 80W
- Installed breathable gland prevents internal moisture accumulation
- Bracket design allows installation without removing mounting bracket
- High efficiency up to 180 Lm/W
- Pre-wired with 1.5 metre of rubber insulated cable for ease of installation



INPUT	HERTZ	TEMP	LIFETIME (HRS)	CRI	SDCM	BEAM ANGLE	CLASS	IP	IK
220/240V	50/60Hz	-30°C to 50°C	L80 100,000	70	5	110° (SYM) 60/120° (ASY)	1	IP66	IK08

CODE	DESCRIPTION	WATTAGE	CCT	LUMENS	LMW	A	B	C	WINDAGE
AAZT1/SYM/1		20W/40W		7200lm (4000K)		319mm	255mm	61mm	0.07
AAZT2/SYM/1		80W		14000lm (4000K)		324mm	311mm	63mm	0.09
AAZT3/SYM/1	CCT Selectable	120W	3000/4000/	22000lm (4000K)	180lm	411mm	318mm	73mm	0.11
AAZT4/SYM/1		160W	5000K	29000lm (4000K)		452mm	333mm	74mm	0.13
AAZT5/SYM/1		240W		44000lm (4000K)		460mm	425mm	75mm	0.17
AAZT6/SYM/1		320W		58000lm (4000K)		496mm	425mm	80mm	0.19

For Asymmetrical versions simply replace **SYM** with **ASY** from the above product codes.

CODE (ACCESSORIES)	DESCRIPTION	CODE (ACCESSORIES)	DESCRIPTION
AAZLED/60PMA	60mm Pole Mount Adaptor	AAZLED/40-90PCA	40-90mm Pole Clamp Accessory 40-160W
AAZLED/76PMA	76mm Pole Mount Adaptor	AAZLED/40-150PCA	40-150mm Pole Clamp Accessory 240W-320W