



Technical Specification



Product Code: ES1RF2 Description: Alarm RF-Link Module 2

RF-Link	ES1RF2 Batch Code: Ad Module with non-r with: ES1SL_ES141	47-031417 S/N: F00005	love	
ES1CL Maximum	or ES1CHL Series ala	ES1MUL, arms only	st to rem	
	et Park, B98 BYN	FUK	there fir	
		CLH	TÜVRheinland	





General Information

deneral information	
Dimensions (mm)	33 x 27 x 53.6
Mounting	Recessed into compatible Espire alarm
Weight (Kg)	0.026
Warranty (Years)	5
Supply, Power & Backup	
Supply Type	Battery Powered
Operating Voltage (V DC)	3
Battery Backup	Non-replaceable 10 Year Battery
Battery Type	3V Lithium
Battery Size	CR123A
Battery Chemistry	Lithium
Interconnectability	
RF-LINK Supported	Built-in
RF-LINK Frequency (MHz)	868.3
RF-LINK Range (Open Field)(m)	100
Maximum Supported Wired & RF-LINK Interconnected Devices	28
Environment	
Operating Temperature (°C)	0 to +40
Relative Humidity Resistance (%)	95 (non-condensing)
Compatible Products Espire Alarms: ES1SL, ES1HL, ES1M	IUL, ES1CHL, ES1CL

Features

Built-in battery to reduce load on battery powered Espire alarms RF-LINK module for Lithium battery powered Espire Alarms

Unit 7 Target Park, Shawbank Road, Lakeside, Redditch B98 8YN United Kingdom **T:** +44 (0)1527 515150 | **F:** +44 (0)1527 515143 **E**: info@espuk.com | **W:** espuk.com



TŪVRheinland

ecification is sub

5 YEAR