


**Technical Specification** 



## Product Code: ES1REMV

Description: Hardwired Interconnect Remote Controller





## **General Information**

General information	
Dimensions (mm)	86 x 86 x 61 (Backbox Included)
Colour	White
Materials	Urea
Mounting	Single Pattress – Surface and Flush Mounting (backbox included)
Weight (Kg)	0.24
Warranty (Years)	5
Supply, Power & Backup	
Supply Type	Mains AC
Supply Voltage (V AC)	230
Frequency (Hz)	50
Cable Size (mm²)	0.75 - 2.5
Maximum Power Consumption (W)	0.5
Standby Power Consumption (W)	0.2
Interconnectability	
Wired Interconnect Supported	Yes
Maximum Interconnect Wiring Distance (m)	300
RF-LINK Supported	No
Maximum Supported Wired & RF-LINK Interconnected Devices	28
Environment	
Operating Temperature (°C)	0 to +40
Relative Humidity Resistance (%)	95 (non-condensing)
Compatible Products Interconnect supported Espire Products	

## Features

3 switches for; testing the alarms, to activate the hush function on & to activate the locate function Compatible with any Espire Interconnect supported Alarms Designed to fit standard UK 1 Gang mount box

Unit 7 Target Park, Shawbank Road, Lakeside, Redditch B98 8YN United Kingdom **T:** +44 (0)1527 515150 | **F:** +44 (0)1527 515143 **E**: info@espuk.com | **W:** espuk.com



TÜVRheinland