

## Luminaires | Ground

### Marker Lights

AU-DK10CS



#### Photometrics

|                           |             |
|---------------------------|-------------|
| <b>Wattage</b>            | 7.5         |
| <b>Lumens</b>             | 375         |
| <b>Lm/W</b>               | 50          |
| <b>Beam Angle</b>         | 130         |
| <b>Colour Temperature</b> | 3000 / 4000 |
| <b>Ra</b>                 | 80          |

#### Product Features

|                          |            |
|--------------------------|------------|
| <b>Brand</b>             | Aurora     |
| <b>IP Rating</b>         | IP67       |
| <b>L70 Hours</b>         | L80 50,000 |
| <b>L80 Hours</b>         | 50000      |
| <b>SKU Type</b>          | Non Dim    |
| <b>Dimmable</b>          | No         |
| <b>Warranty</b>          | 5 Years    |
| <b>Country of Origin</b> | CN         |

#### Electrical Specification

|                            |     |
|----------------------------|-----|
| <b>Input Voltage (Min)</b> | 220 |
|----------------------------|-----|

|                          |     |
|--------------------------|-----|
| Input Voltage (Max)      | 240 |
| Output Voltage           | DC  |
| Input Voltage Type       | AC  |
| Power Factor             | 0.5 |
| Surge Protection (kV)    | 0.5 |
| Protection Class         | 2   |
| Frequency (Min) Hz.      | 50  |
| Frequency (Max) Hz.      | 60  |
| Operating Temp. (Min) °C | -20 |
| Operating Temp. (Max) °C | 40  |

## Physical Attributes

|                           |                     |
|---------------------------|---------------------|
| Height (mm)               | 35                  |
| Overall Diameter (mm)     | 39                  |
| Cutout Diameter Min. (mm) | 25                  |
| Cutout Diameter Max. (mm) | 25                  |
| Material                  | Polycarbonate       |
| Optic Material            | Polycarbonate       |
| Finish Colour             | 304 Stainless Steel |