Knightsbridge





CPL18CT

www.mlaccessories.co.uk



MLA PART CODE	CPL18CT
DESCRIPTION	230V 18W CCT Adj Circular LED Panel- 217mm
NET WEIGHT (KG)	0.38
FINISH	White
DIFFUSER	Opal
DIMENSIONS (MM)	Diameter - 217 Height - 15 Projection - 15 Base Diameter - 172 Recessed Depth - 0 Minimum Void - 50
CUT-OUT (MM)	Cut-out Diameter - 55 Min./Max. Cut-out - 55 - 175
CONSTRUCTION	Construction - Polycarbonate
CLASS	
IP RATING	IP20
WATTAGE (W)	18
LAMP TECHNOLOGY	SMD LED
LAMP INCLUDED	Yes
LUMENS (LM)	1300/1400/1360
LUMENS LIGHT SOURCE ONLY (LM)	2345
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	130
CIRCUIT WATTAGE (W)	18.1
ССТ	3000/4000/6000K
LIGHT COLOUR	CCT
CRI	>85
SDCM	<6
RUNNING CURRENT (A)	0.089
DISPLACEMENT FACTOR	>0.9
SVM	0.17



ML Accessories Ltd. reserves the right to withdraw, improve, or modify any design without prior notification. ML Accessories Ltd. cannot be held responsible for the incorrect application of any product.



Knightsbridge

PST-LM	0.288
BEAM ANGLE (DEGREES)	120
LIFE SPAN (HRS)	30,000
L70B50 LIFESPAN (HRS)	30,000
DIMMABLE	No
IC RATED	Yes
OPERATING TEMPERATURE	-20~40°C
INPUT VOLTAGE	230V 50Hz
CABLE LENGTH (M)	0.3
WARRANTY	3year(s)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5055832984092
Date Created: 03/03/2025 14:11	·

Date Created: 03/03/2025 14:11





