

Luminaires | Downlights

Poly-SlimCS™ 6W Colour Switchable Round Polycarbonate Low Profile Downlight

AU-PLPC06CS



Photometrics

Wattage	6
Lumens	510 - 550
Lm/W	92
Beam Angle	120
Colour Temperature	3000 / 4000 / 6500
RA	80
SDCM	<10
UGR	NO

Product Features

Brand	Aurora
IP Rating	IP40
IK Rating	ik02
L70 Hours	L70 40,000
Lifetime Class	B50
SKU Type	Non Dim
Dimmable	no
Warranty	3 Years

Country of origin	CN
-------------------	----

Electrical Specification

Input Voltage (Min)	220
Input Voltage (Max)	240
Input Voltage Type	AC
Power Factor	0.5
Surge Protection (kV)	1500V
Protection class	CLASS 3
Frequency (Min) Hz.	50HZ
Frequency (Max) Hz.	60HZ
Operating Temp. (Min) °C	-20
Operating Temp. (Max) °C	40

Physical Attributes

Length (mm)	128
Height (mm)	25
Overall Diameter (mm)	128
Cutout Diameter Min. (mm)	115
Cutout Diameter Max. (mm)	115
Material	Polycarbonate
Optic Material	Opal Polycarbonate
Diffuser	Opal
Finish Colour	White