

Luminaires | Downlights

Uni-FitCS™ Colour Switchable 23W Fixed Polycarbonate Downlights

AU-DL23CS



Photometrics

Wattage	23
Lumens	2500 - 2700
Lm/W	117
Beam Angle	100
Colour Temperature	3000 / 4000 / 6500
Ra	650
SDCM	<10
UGR19	No

Product Features

Brand	Aurora
IP Rating	IP44
IK Rating	IK02
L70 Hours	L70 40,000
Lifetime Class	B50
SKU Type	Non Dim
Dimmable	No
Warranty	5 Years

Country of Origin	CN
-------------------	----

Electrical Specification

Input Voltage (Min)	220
Input Voltage (Max)	240
Input Voltage Type	AC
Power Factor	0.9
Surge Protection (kV)	1500
Protection Class	class 2
Frequency (Min) Hz.	50HZ
Frequency (Max) Hz.	60HZ
Operating Temp. (Min) °C	-20
Operating Temp. (Max) °C	40
Glow Wire Test (°C)	No

Physical Attributes

Height (mm)	65
Overall Diameter (mm)	200
Lamp Base	LED
Cutout Diameter Max. (mm)	170
Material	Polycarbonate
Optic Material	Polycarbonate
Diffuser	Opal
Finish Colour	White