



Colour switchable between 2700K, 3000K and 4000K



Wattage Switchable between 4W & 6W



Switches allow you to choose

WARRANTY

Warranty

7 years

FEATURES & BENEFITS

Tilttable to highlight features on walls

2-part connector provides first fix wiring whilst the luminaire is detached from the connector, loop in loop out, quick maintenance should disconnection/reconnection be required

High efficacy of 130lm/W

Compatible with Click Flow CT100 series

TRIAC Mains dimmable

Fixed with 55 degree beam angle

H4 LITE CSP

Colour & Wattage Switchable using switches on bottom of product

FEATURES

IP rating	IP65 (from below) IP20 (from above)
CSP Switchable	Switchable CCT
Tilttable	30°
Dimmable Option	Yes (TRIAC)
LED Lifetime	L70 60,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM4
Emergency Option	No
Rotation Angle	No

INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	-20°C - 40°C
Weight	235g
Insulation Coverable	Rolled and blown insulation
Double Insulation	Yes
Inrush Current	1.4A
Cut Out Size	70mm - 72mm
Construction Material	Mild steel / V0 rated plastic
UK Bathroom Zone	1
Maximum ceiling thickness	40 mm
SELV	No
Electric Class (1, 2, 3)	2
Suitable for coastal areas	No
Install Connector Type	2 part first fit connector
UK Building Regulations	Part B, C, E, P & L RE2020, EN 13141-1:2004, EN 1345-2:2014, EN ISO 10140-2/3:2010
FR Building Regulations	
Mounting Options	Recessed Solid Timber 30/60/90min, I-Joist 30min, Metal Web 30min
Part B Fire Rating	
Power Factor	0.85

Photometrics @ 25°C

Product Code	Finish	Beam	W	Colour	lm	lm/W	Energy
DLT661600A	White bezel included	55°	4W	2700K	450	112	
				3000K	520	130	
				4000K	500	125	
			6W	2700K	650	108	
				3000K	750	125	
				4000K	720	120	

WIRING INFORMATION

Cable / Flying Lead	0.75mm² - 2.5mm² 3 core cable for connector
Cable Required for Connector	Push-fit terminal for: Twin & Earth (6242Y 2x1.5mm²) or 3-core cable (R02V 3x1.5mm²)
Type of Wiring Required	Parallel

ACCESSORIES

DLT661BLKBZ	Black Bezel	Sold Separately
DLT661BSBZ	Brushed Steel Bezel	Sold Separately
DLCVT110	Concealer ring for larger cut outs	Sold Separately
DM298FP	Faceplate dimmer	Sold Separately
DM298GRID	Grid dimmer	Sold Separately

BEAM ANGLE: 55°

