

JC23401WPRDIM

RadiaLED Utility

RadiaLED Utility Mains IP65 Ø205mm Bulkhead 12W 4000K 1150lm LED Pris DALI/1-10v

Features & Benefits

- IP65 weather resistant
- Anti-vandal construction
- Corrosion resistant
- suitable for coastal locations
- · Opal or prismatic polycarbonate diffuser options
- Dusk to dawn on/off photocell options available
- Up to 95 lumens per circuit Watt





Trade Name











RadiaLED



General Information

Mounting Wall

Environment Outdoor

Suitable For Zones Zones 1 and 2

Product Group LED - Surface

Color Finish White

Product Shape Round

Product Range RadiaLED Utility

Overall Dimensions 203 x 85mm

Height (mm) 85

Diameter (mm) 203
Product Weight(kg) 0.5

Light Source LED

Light Source Features Neutral White

Recommended product location Suitable for indoor or outdoor use, wall and ceiling mount

Method of fix Back fix using screws provided

IP Rating IP65

Origin of manufacturer Made in China

Warranty 5 Year Warranty (See Website for terms and conditions)

Dimming Protocol Compatibility DALI/1-10V

Driver manufacturer Kreat

LED manufacturer/type

Lighting Product Type 1

Customs Tariff code**

2835/HONGLI

Surface Light

9405119090

Electrical

Voltage Rating 220-240
Primary Running Current(Amp) 0.065

Inrush current(Amps) 8A

Operating Frequency Hz 50/60Hz

Secondary running current(mA)

Constant Current or Constant Voltage

CC

Luminaire Circuit Wattage1

12

Class I
Total Harmonic Distortion (THD)% 0.12

EMC Compliant (EN55015) yes

Power Factor Correction 0.9

Input Electrical Connections live, earth, neutral screw terminal (2 x conduit entry points)

Dimmable Yes

Thermals

Thermal Cut Out yes

Operating Temperature Range °C -25 to +50

Performance Data

LED Life (Hours)* 30000

This product contains a light source of energy efficiency

Energy Rating

class F

Actual Lumen Output1 1150
Lumens Per Circuit Watt1 96

Color Rendering Index 80-89

CRI: Ra **80**

Correlated Colour Temperature1 4000K

Beam Angle ° 120

LOR (Light Output Ratio) % 100

Photometry Available **yes**

Controls and Sensors

Control Networkable Control

Construction

Primary Material
Outer Diffuser

Heat Sink

Driver Housing

Polycarbonate

Polycarbonate

Aluminium

polycarbonate

Packaging

Quantity Per Outer Carton

Product Bar Code EAN-13 Number

Outer carton Bar Code ITF-14 Number

12

5052544100499

15052544100496

Standards & Approvals

Manufactured in accordance to

CE Marked

UKCA Marked

Date code/Purchase order No.

WEEE symbol

Certificate Of Conformity

Accredited Members

BS EN 60598-2-1

yes


Yes


Yes

yes

Available on request

LIA, ISO9001-2015, ISO14001-2015







of lumen depreciation during the warranty period.

**JCC Lighting Limited makes every effort to ensure that the Customs Tariff information in this document is timely and accurate. However, it's not possible for us to assure the absolute veracity and completeness of that information, as errors may occur. The placement of any inaccurate tariff information is completely unintentional. JCC Lighting Limited reserves the right, in its sole discretion, to correct any errors or omissions to the tariff code and to make any and all changes contained in this document at any time and without notice. It is the sole responsibility of the importer to ensure that the commodity code advised is correct for the products/goods being supplied by JCC Lighting Limited. JCC Lighting Limited does not assume any liabilities, losses, costs, and expenses arising out of or related to the importers use of this commodity code or the information related to the import of any JCC Lighting products.

JCC Lighting LTD, Lux Park, Chichester Business Park, City Fields Way, Tangmere, Chichester, West Sussex, PO20 2FT. Sales: 01243 838999 (8am to 5pm Monday to Friday) Fax: 01243 838998 | sales@jcc.co.uk | www.jcc.co.uk Company Registration Number: 03044848 | VAT Number: 918544112

This document is uncontrolled if printed, all information is subject to change

Version 135 [26/03/2025]