

JC077008SIL

Line Of Light

Line of Light 1200mm 40W IP20 3000/4000/5700K DALI/Switch Dim Silver



Features & Benefits

- Two-part construction allowing easy access to termination and internal components
- Available in 4ft and 5ft lengths
- Available in white, silver and black
- Colour selectable between 3000K, 4000K & 5700K
- Illuminated corners & upward illumination options
- Suspension kit available
- Linking kit (JC077156) available to assemble longer lengths, squares and rectangle configurations
- Sections and corners can be connected via a simple plug and play system
- For longer seamless runs add /EXT to any standard Line of Light product codes to order middle/end pieces that exclude end caps and flex



General Information

Mounting	Surface or Suspended
Suitable For Zones	Outside Zone 2
Product Group	Commercial Linear
Color Finish	Silver
Product Shape	Rectangular
Product Range	Line Of Light
Overall Dimensions	1205 x 60 x 78
Length (mm)	1205
Width (mm)	60
Height (mm)	78
Light Source	LED
Light Source Features	3CCT Selectable
Additional Information	It is advised not to mix 1205mm and 1505mm fittings on the same connected layout- surface diffuser brightness may vary between the different lengths

Luminaire Accessories

Fixing centres

IP Rating

Origin of manufacturer

Warranty

Dimming Protocol Compatibility

Driver manufacturer

LED manufacturer/type

Customs Tariff code**

Electrical

Voltage Rating

Primary Running Current(Amp)

Inrush current(Amps)

Operating Frequency Hz

Secondary running current(mA)

Constant Current or Constant Voltage

Luminaire Circuit Wattage1

Class

Output Voltage Max/Range (VDC)

Total Harmonic Distortion (THD)%

EMC Compliant (EN55015)

Power Factor Correction

Input Electrical Connections

Dimmable

Thermals

Thermal Cut Out

Operating Temperature Range °C

Performance Data

LED Life (Hours)*

Energy Rating

Actual Lumen Output1

Lumens Per Circuit Watt1

Color Rendering Index

CRI: Ra

Correlated Colour Temperature1

Correlated Colour Temperature2

Correlated Colour Temperature3

Beam Angle °

LOR (Light Output Ratio) %

JC077156 linking kit, JC077150 Corner(add BLK/SIL/WH),

JC077153 2m suspension kit(add BLK/SIL/WH), JC077154

5m suspension kit(add BLK/SIL/WH)

See instruction hseet

20

China

5 Year Warranty(Terms & conditions apply)

DALI/Sw dim

BOKE

Shaanxi/2835

9405119090

220-240

0.3

4.75A peak ,162us duration(50 % Ipeak)

50/60Hz

550-1300

CC

40

I

6-42

10

Yes

0.95

Live, Earth, Neutral

DALI-2(DT-6)/Switch dim

yes

-20 to 60

50000

This product contains a light source of energy efficiency class D

4650

116

80-89

80

3000

4000

5700

75

100

Photometry Available

Yes

Construction

Primary Material
Outer Diffuser
Driver Housing

Aluminium
Polycarbonate
Polycarbonate

Packaging


Product Bar Code EAN-13 Number


5052544125508

Standards & Approvals

Manufactured in accordance to
CE Marked
UKCA Marked
Date code/Purchase order No.
WEEE symbol
Certificate Of Conformity
Accredited Members

BS EN 60598-2-1
Yes
Yes
Yes
Yes
Available on request
LIA, ISO9001-2015, ISO14001-2015





*Hours life stated is an indication of expected L70 chip and light output calculations when operating in optimum conditions. Product warranty period supports the full product during the term given. The L70 hours expectancy is not correlated with the full product warranty term, nor is it a representation of lumen depreciation during the warranty period.

**JCC Lighting Limited makes every effort to ensure that the Customs Tariff information in this document is timely and accurate. However, it's not possible for us to assure the absolute veracity and completeness of that information, as errors may occur. The placement of any inaccurate tariff information is completely unintentional. JCC Lighting Limited reserves the right, in its sole discretion, to correct any errors or omissions to the tariff code and to make any and all changes contained in this document at any time and without notice. It is the sole responsibility of the importer to ensure that the commodity code advised is correct for the products/goods being supplied by JCC Lighting Limited. JCC Lighting Limited does not assume any liabilities, losses, costs, and expenses arising out of or related to the importers use of this commodity code or the information related to the import of any JCC Lighting products.

JCC Lighting LTD, Lux Park, Chichester Business Park, City Fields Way, Tangmere, Chichester, West Sussex, PO20 2FT.

Sales: 01243 838999 (8am to 5pm Monday to Friday) Fax: 01243 838998 | sales@jcc.co.uk | www.jcc.co.uk

Company Registration Number: 03044848 | VAT Number: 918544112

This document is uncontrolled if printed, all information is subject to change

Version 130 [26/03/2025]