


JC091021

## Niteflood CCT Floodlights

Niteflood™ LED Floodlight 30W IP65 3000K / 4000K / 5700K CCT Black

### Features & Benefits

- 3CCT Switchable colour temperature
- Up to 112 LpcW
- IP65 protection against dust and moisture
- 60° angled bracket for ease of installation
- Breather gland incorporated to protect against condensation
- Opal glass for reduced glare
- Supplied pre-wired with 800mm flex
- Driverless technology
- PIR versions, with manual override available



### General Information

Mounting	Wall Mount
Environment	Exterior
Product Group	LED Floodlights
Color Finish	Black
Product Shape	Rectangular
Product Range	Niteflood
Overall Dimensions	139 x 173.6 x 61.8
Width (mm)	173.6
Height (mm)	139
Depth (mm)	61.8
Product Weight(kg)	0.497
Light Source	LED
Light Source Features	CCT Switchable
Recommended product location	Exterior Wall Mount for security lighting
Method of fix	Screws/Rawl plugs

Fixing centres	See profile drawing
IP Rating	IP65
Origin of manufacturer	China
Warranty	3 Year Warranty (See Website for terms and conditions)
Mounting height	2.5m max
Driver manufacturer	No driver, mains LED Chips
LED manufacturer/type	Smalite 2835
Customs Tariff code**	9405421000

## Electrical

Voltage Rating	220-240
Operating Frequency Hz	50/60Hz
Luminaire Circuit Wattage1	30
Class	I
EMC Compliant (EN55015)	Yes
Power Factor Correction	0.8
Input Electrical Connections	Live, Earth, Neutral

## Thermals

Operating Temperature Range °C	-10 to 30
--------------------------------	-----------

## Performance Data

LED Life (Hours)*	54000
Energy Rating	This product contains a light source of energy efficiency class E
Actual Lumen Output1	3200
Lumens Per Circuit Watt1	107
Standard Deviation Colour Matching - SDCM	<5
Color Rendering Index	80-89
CRI: Ra	83
Correlated Colour Temperature1	3000
Correlated Colour Temperature2	4000
Correlated Colour Temperature3	5700K
LOR (Light Output Ratio) %	100
Photometry Available	Yes, available on request

## Construction

Primary Material	Aluminium
Outer Diffuser	Opal toughened glass
Heat Sink	Aluminium



## Packaging

Product carton overall dimensions(cm)	17.7 x 5.3 x 15cm
Product Packaged Weight(kg)	0.56

Quantity Per Outer Carton	20
Outer carton(L)- cm	37.5
Outer carton(W)- cm	19.2
Outer carton(H)- cm	37
Outer carton Net weight- kg	9.94
Outer carton Gross weight- kg	10.51

Standards & Approvals

Manufactured in accordance to	BS EN 60598-2015,2-1,2-5
CE Marked	Yes
UKCA Marked	Yes
Date code/Purchase order No.	Yes
WEEE symbol	Yes
Certificate Of Conformity	Available on request
Accredited Members	LIA, ISO9001-2015, ISO14001-2015
Approvals	Independently tested to ISO9227:2022 Neutral salt spray corrosion testing



Non-replaceable light source



\*Hours life stated is an indication of expected L70 chip and light output calculations when operating in optimum conditions. Product warranty period supports the full product during the term given. The L70 hours expectancy is not correlated with the full product warranty term, nor is it a representation of lumen depreciation during the warranty period.

\*\*JCC Lighting Limited makes every effort to ensure that the Customs Tariff information in this document is timely and accurate. However, it's not possible for us to assure the absolute veracity and completeness of that information, as errors may occur. The placement of any inaccurate tariff information is completely unintentional. JCC Lighting Limited reserves the right, in its sole discretion, to correct any errors or omissions to the tariff code and to make any and all changes contained in this document at any time and without notice. It is the sole responsibility of the importer to ensure that the commodity code advised is correct for the products/goods being supplied by JCC Lighting Limited. JCC Lighting Limited does not assume any liabilities, losses, costs, and expenses arising out of or related to the importers use of this commodity code or the information related to the import of any JCC Lighting products.

---

JCC Lighting LTD, Lux Park, Chichester Business Park, City Fields Way, Tangmere, Chichester, West Sussex, PO20 2FT.

Sales: 01243 838999 (8am to 5pm Monday to Friday) Fax: 01243 838998 | [sales@jcc.co.uk](mailto:sales@jcc.co.uk) | [www.jcc.co.uk](http://www.jcc.co.uk)

Company Registration Number: 03044848 | VAT Number: 918544112

This document is uncontrolled if printed, all information is subject to change

Version 55 [26/03/2025]