

JC130014

Commercial Wall Pack Bulkhead

Novium 5W 3000/4000K IP65 Black

Features & Benefits

- Multiple Wattage selectable
- Two colour selectable
- Downward beam angle aids in reduction of light pollution
- IP65 and IK10
- Up to 144 LpcW
- Emergency and photocell option available





General Information

Mounting	Wall mounted
Environment	Demanding
Suitable For Zones	Suitable for inside Zone 1
Product Group	LED Bulkhead
Color Finish	Black
Product Range	LED Wall Pack Bulkhead
IK Rating	IK10
Overall Dimensions	128 x 105 x 67 mm
Width (mm)	128
Height (mm)	105
Depth (mm)	67
Light Source	LED
Light Source Features	Colour Selectable
Recommended product location	Exterior wall mount
Method of fix	Screw fix

IP Rating	IP65
Origin of manufacturer	China
Warranty	5 Year Warranty (See Website for terms and conditions)
Driver manufacturer	TCI
LED manufacturer/type	2835
Lighting Product Type 1	Wall Mount
Customs Tariff code**	9405119090

Electrical

Voltage Rating	220-240
Primary Running Current(Amp)	0.025
Inrush current(Amps)	15
Operating Frequency Hz	50/60Hz
Secondary running current(mA)	350
Constant Current or Constant Voltage	CC
Luminaire Circuit Wattage1	5
Class	I
Output Voltage Max/Range (VDC)	11.6-12.8
EMC Compliant (EN55015)	Yes
Power Factor Correction	0.7
Input Electrical Connections	Live, neutral, earth
Dimmable	No

Thermals

Operating Temperature Range °C

Performance Data

LED Life (Hours)*	54000
Energy Rating	This product contains a light source of energy efficiency
	class D
Actual Lumen Output1	585
Lumens Per Circuit Watt1	144
Standard Deviation Colour Matching - SDCM	>6
CRI: Ra	80
Correlated Colour Temperature1	3000
Correlated Colour Temperature2	4000K
Beam Angle °	104
Photometry Available	Yes

-20 to +40

Construction


Primary Material	Aluminium
Outer Diffuser	Polycarbonate
Driver Housing	Polycarbonate

Packaging


Product carton overall dimensions(cm)	13.5 x 11.5 x 7.5cm
Product Packaged Weight(kg)	0.32
Quantity Per Outer Carton	20
Outer carton(L)- cm	28.5
Outer carton(W)- cm	24
Outer carton(H)- cm	40
Outer carton Net weight- kg	6.4
Outer carton Gross weight- kg	7.7
Product Bar Code EAN-13 Number	5052544129506
Outer carton Bar Code ITF-14 Number	15052544129503

Standards & Approvals

Manufactured in accordance to	BS EN 60598-2-1
CE Marked	Yes
UKCA Marked	Yes
Date code/Purchase order No.	Yes
WEEE symbol	Yes
Certificate Of Conformity	Available on request
Accredited Members	LIA, ISO9001-2015, ISO14001-2015







*Hours life stated is an indication of expected L70 chip and light output calculations when operating in optimum conditions. Product warranty period supports the full product during the term given. The L70 hours expectancy is not correlated with the full product warranty term, nor is it a representation of lumen depreciation during the warranty period.

**JCC Lighting Limited makes every effort to ensure that the Customs Tariff information in this document is timely and accurate. However, it's not possible for us to assure the absolute veracity and completeness of that information, as errors may occur. The placement of any inaccurate tariff information is completely unintentional. JCC Lighting Limited reserves the right, in its sole discretion, to correct any errors or omissions to the tariff code and to make any and all changes contained in this document at any time and without notice. It is the sole responsibility of the importer to ensure that the commodity code advised is correct for the products/goods being supplied by JCC Lighting Limited. JCC Lighting Limited does not assume any liabilities, losses, costs, and expenses arising out of or related to the importers use of this commodity code or the information related to the import of any JCC Lighting products. JCC Lighting LTD, Lux Park, Chichester Business Park, City Fields Way, Tangmere, Chichester, West Sussex, PO20 2FT. Sales: 01243 838999 (8am to 5pm Monday to Friday) Fax: 01243 838998 | <u>sales@jcc.co.uk</u> | <u>www.jcc.co.uk</u> Company Registration Number: 03044848 | VAT Number: 918544112

This document is uncontrolled if printed, all information is subject to change

Version 38 [26/03/2025]