



DATASHEET



SPKEVFS10

SpektroLED Evo Fixed - Pack of 10 - Fire Rated IP65 Downlight with 2 x Wattage and 4 x CCT in white

www.mlaccessories.co.uk



MLA PART CODE	SPKEVFS10
DESCRIPTION	SpektroLED Evo Fixed - Pack of 10 - Fire Rated IP65 Downlight with 2 x Wattage and 4 x CCT in white
NET WEIGHT (KG)	2.32
DIFFUSER	Prismatic
DIMENSIONS (MM)	Diameter - 90 Recessed Depth - 43 Minimum Void - 50
CUT-OUT (MM)	Cut-out Diameter - 70
CONSTRUCTION	Construction - Pressed steel
CLASS	II
IP RATING	IP65 (IP20 from above)
WATTAGE (W)	5/7
LAMP TECHNOLOGY	SMD LED
LUMENS (LM)	580/600/630/620, 780/810/870/840
LUMENS LIGHT SOURCE ONLY (LM)	1020
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	144
CIRCUIT WATTAGE (W)	7.1
CCT	2700/3000/4000/6000K
LIGHT COLOUR	CCT
CRI	>80
SDCM	<6
RUNNING CURRENT (A)	0.037
DISPLACEMENT FACTOR	>0.7
SVM	0.008
PST-LM	0.297
BEAM ANGLE (DEGREES)	60
L70B10 LIFESPAN (HRS)	50,000
DIMMABLE	Yes*

FIRE-RATED	Tested to 30/60/90 minutes
I-JOIST RATED	30 minutes
WEB-JOIST RATED	30 minutes
IC RATED	Yes
ACOUSTIC RATED	Yes
OPERATING TEMPERATURE	25°C
INPUT VOLTAGE	230V 50Hz
WARRANTY	7year(s)
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270841183

Date Created: 13/05/2025 08:57

