

# Acti9 Isobar P A - distribution board - 14 way SP+N

Local distributor code: 405638954

EAN Code: 5018934007540

### Main

| Range                     | Acti9   |
|---------------------------|---|
| Product name              | Acti9 Isobar P A  |
| Product or component type | Distribution board  |
| Device application        | Distribution  |
| Enclosure type            | Standard  |
| Door type                 | Overall   |
| Provided equipment        | Earth stud Enclosure Door Front cover Pan assembly Neutral terminal block Earth terminal block Blanking plate |
| Colour                    | Cream (RAL 9001)  |

| Complementary                          |  |
|--|--|
| Enclosure mounting                     | Surface  |
| Poles description                      | 1P + N   |
| [le] rated operational current         | 125 A at 230/240 V AC  |
| Breaking capacity                      | 25 kA  |
| Overvoltage category                   | IV   |
| [Ui] rated insulation voltage          | 500 V  |
| [Uimp] rated impulse withstand voltage | 6 kV   |
| Incomer device options                 | Switch disconnector - 2P Terminal block - 2P RCCB - 2P   |
| Protection device options at outgoer   | Miniature circuit breaker (MCB) 63 A Residual current circuit breaker with overcurrent protection (RCBO) 45 A 100 mA Residual current circuit breaker with overcurrent protection (RCBO PoN) 45 A 100 mA |
| Number of ways                         | 14 ways (1P) outgoer   |
| Enclosure material                     | Steel  |
| Surface treatment                      | Ероху  |
| Surface finish                         | Powder paint   |

| Height     | 300 mm |
|------------|--------|
| Width      | 417 mm |
| Depth      | 117 mm |
| Net weight | 4.8 kg |

#### **Environment**

| IP degree of protection               | IP20 internal conforming to BS EN 60529 IP3x external conforming to BS EN 60529 |
|---------------------------------------|---|
| IK degree of protection               | IK05  |
| Pollution degree                      | 3   |
| Ambient air temperature for operation | -3570 °C  |
| Ambient air temperature for storage   | -4080 °C  |

# **Packing Units**

| Unit Type of Package 1       | PCE        |
|------------------------------|------------|
| Number of Units in Package 1 | 1          |
| Package 1 Height             | 13.000 cm  |
| Package 1 Width              | 42.500 cm  |
| Package 1 Length             | 30.500 cm  |
| Package 1 Weight             | 5.718 kg   |
| Unit Type of Package 2       | PAL        |
| Number of Units in Package 2 | 48         |
| Package 2 Height             | 93.000 cm  |
| Package 2 Width              | 100.000 cm |
| Package 2 Length             | 120.000 cm |
| Package 2 Weight             | 299.464 kg |

# Offer Sustainability

| Sustainable offer status        | Green Premium product  |
|---------------------------------|--|
| REACh Regulation                | REACh Declaration  |
| EU RoHS Directive               | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration                     |
| Mercury free                    | Yes  |
| China RoHS Regulation           | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |
| RoHS exemption information      | Yes  |
| <b>Environmental Disclosure</b> | Product Environmental Profile  |

## **Contractual warranty**

Warranty 18 months

# Recommended replacement(s)