define®

Technical Specification

CLiCK® Scolmore GROUP

Product Code: FPCH504WH

Luckinslive 393319301

Description: 50A Ingot 2 Gang Double Pole Switch With 13A Double Pole Switched Socket Outlet





General Information

Plate Dimensions (mm)	146 (W) x 88 (H) x 1.3 (D)		
Dimensions With Gasket (mm)	146 (W) x 88 (H) x 3 (D)		
Plate Fixing Centres - Horizontal (mm)	120.6		
Style	Flat Plate		
Finish	Polished Chrome		
Insert Colour	White		
Gasket Colour	Transparent (Neoprene)		
Materials	Front Plate: Stainless Steel	Insert & Rear Housing: Urea	
	Terminals: Brass	Terminal Screws: Steel & Yellow Passivated	
	Contacts: Silver "on-lay" Copper / Brass	Internal Busbars: Formed Pressed Brass	
	Earth Strap: Mild Steel		
Anti Microbial Certified	No		
Operating Voltage (AC)	250	Frequency (Hz)	50
Resistive Load Rating (A)	50		
Termination Type	Screw		
Terminal Size (mm)	Ø6	Terminal Torque Value (Nm)	2.5
Terminal Capacity - Solid (mm^2)	1 x 16		
Double Pole Switch	Yes		
Twin Earth Terminals	Yes		
Product Marking	Cooker		
Minimum Back Box Depth (mm)	47		
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	20		

Standards BS 4177

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
T: +44 (0)1827 63454 | **F:** +44 (0)1827 63362
E: sales@scolmore.com | **W:** scolmore.com

CE UKCA

Catalogue Range DoC Installation