

Product Code: SFBS551BK

Description: 13A Ingot Double Pole Switched Fused Connection Unit With Optional Flex Outlet



General Information

Insert Dimensions (mm)	82.5 (W) x 82.5 (H) x 2.5 (D)	
Plate Dimensions (mm)	86 (W) x 86 (H) x 4 (D)	
Plate Fixing Centres - Horizontal (mm)	60.3	
Style	Screwless Complete	
Finish	Brushed Stainless	
Insert Colour	Black	
Compatible Cover Plate	SCP151#	
Materials	Cover Plate: Stainless Steel Rear Housing: Urea Terminals: Brass Contacts: Silver "on-lay" Copper / Brass Earth Strap: Mild Steel	Insert: Polycarbonate Switch & Fuse Drawer Cover: Stainless Steel Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass
Anti Microbial Certified	No	
Rated Voltage (V~) (Ue)	250	Frequency (Hz) 50
Resistive Load Rating (A)	13	
Fuse Fitted Rating & Type	13A (BS 1362)	
Termination Type	Screw	
Terminal Size (mm)	Ø5	Terminal Torque Value (Nm) 2
Terminal Capacity - Solid (mm²)	3 x 2.5 or 2 x 4	
Switched	Yes	
Double Pole Switch	Yes	
Twin Earth Terminals	Yes	
Product Marking	Fused	
Flex Outlet Available	Yes	
Flex Outlet Location	Front of Plate	Flex Outlet Dimension (mm) Ø10
Minimum Back Box Depth (mm)	35	
Ingress Protection	IP20	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	10	
Standards	BS 1363-4 BS 1362	

Additional Information	For cleaning / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.
-------------------------------	--