

Product Code: SFPW156PW

Technical Specification

Non-Isolated Single Satellite Outlet Description:





Insert: Polycarbonate

Terminals: Brass

General Information

Insert Dimensions (mm) $82.5 \text{ (W)} \times 82.5 \text{ (H)} \times 2.5 \text{ (D)}$ Plate Dimensions (mm) $86 \text{ (W)} \times 86 \text{ (H)} \times 4 \text{ (D)}$

Plate Fixing Centres - Horizontal (mm) 60.3

Style Screwless Complete

Finish Polar White Insert Colour Polar White

Compatible Cover Plate SCP231#

Materials Cover Plate: Polycarbonate

Earth Plate: Mild Steel

Anti Microbial Certified No

Termination Type Screw

Isolated No

Non-Isolated Yes

Non-Isolated Comments Enables 2 way signal transmission

Shielded No

Minimum Back Box Depth (mm) 25

Ingress Protection IP20

Operational Temperature (°C) -5 to +40

Warranty (Years) 10

Additional Information For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram

with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. Isolated socket will filter out any interference, if a 2 way signal is required, i.e. for use with satellite hard

wire extensions, then a non-isolated outlet is required.



