



AFRLED170/CW

Freska Downlight Cool White 170mm White



Features

Economic ultra-slim circular LED performance downlight suitable for semi commercial applications

Ideal for use in areas with shallow ceiling void.

Remote driver with plug and play connection

Edge lit providing excellent uniform illumination

Non-dimmable

Optional plug-in self-test emergency pack suitable for all three models

General Information

| | |
|--------------------------------|-----------------|
| Lamp Type | LED |
| Colour / Finish | White |
| IP Rating | IP44 |
| IK Rating | IK02 |
| Class Protection | 2 |
| Internal / External | Internal |
| Surface / Recessed / Suspended | Recessed |
| Lifetime (Hrs) | L70 B50 60,000h |
| Warranty (Years) | 3 |
| CE Mark | Yes |
| Diameter (mm) | 180 mm |
| Height (mm) | 25 mm |
| Accessories | AFRLED/M3/ST |

Technical Information

| | |
|------------------|---------------|
| Wattage | 13W |
| Lumens Delivered | 1000lm |
| Lm/W | 81lm/W |
| Beam Angle | 110 |
| CRI | 80 |
| CCT | 4000K |
| Input | 220/240V |
| Hertz | 50/60Hz |
| Operating Temp | -10°C to 25°C |
| SDCM | 5 |
| UGR | 27 |



