



Comfort EVO 2 Dual Output CCT Downlight White



- Economic high performance CCT selectable IP44 downlight suitable for commercial and healthcare applications
- Intelligent and eco-friendly 3 part design allows end user the choice of either black or white reflector and trim accessories to add to the downlight (ACOM*/1), offering great customisation and product upgradability
- Deep cut-off angle for glare control and comfort
- CCT selectable between 3000K and 4000K and power selectable; offering a choice of 2 outputs, in one luminaire
- Downlight design allows installation into existing hole cut-outs of 210mm
- Anti-Ligature kit available for installation in secure environments such as healthcare and educational facilities
- Polycarbonate housing with unique thermal management for durability and optimum lifespan
- Dimmable and Emergency options, standard and Self-Test Emergency available using the Hawk Kit Emergency Pack

General Information

Lamp Type	LED
IP Rating	IP44
Class Protection	2
Internal / External	Internal



Surface / Recessed / Suspended	Recessed
OCTO Category	OCTO options available
Warranty (Years)	5
Material	Aluminium, Polycarbonate
Technical Information	
Wattage	17W - 21W
Lumens Delivered	2300lm - 2800lm (4000K)
Lm/W	130lm/W (4000K)
Beam Angle	80
CRI	80
CCT	3000/4000K
Input	220/240V
Hertz	50/60Hz
Operating Temp	-20°C to 25°C
Lumen Depreciation	L80 60,000h
Power Factor	0.85