




Product Description:

InterLedCS[™] 30W Colour Switchable 1200mm Batten


Suitable for a range of commercial applications, the new InterLED^{CS}[™] has a colour switch to simply select between 3000K, 4000K and 6500K. Opal polycarbonate diffuser ensures uniform light distribution. Available in a choice of white or black finish, with an emergency self test option.

SKU Code	Wattage	Colour	Lumens	Beam Angle	Finish Colour	SKU Type
AU-LN1230CSBLK	30	3000K	3260	110	Black	Non Dimmable
AU-LN1230CSBLK	30	4000K	3410	110	Black	Non Dimmable
AU-LN1230CSBLK	30	6500K	3300	110	Black	Non Dimmable
AU-LN1230CSEMBLK	30	3000K	3260	110	Black	Emergency Self-Test
AU-LN1230CSEMBLK	30	4000K	3410	110	Black	Emergency Self-Test
AU-LN1230CSEMBLK	30	6500K	3300	110	Black	Emergency Self-Test
AU-LN1230CSEMW	30	3000K	3260	110	White	Emergency Self-Test
AU-LN1230CSEMW	30	4000K	3410	110	White	Emergency Self-Test
AU-LN1230CSEMW	30	6500K	3300	110	White	Emergency Self-Test
AU-LN1230CSW	30	3000K	3260	110	White	Non Dimmable
AU-LN1230CSW	30	4000K	3410	110	White	Non Dimmable
AU-LN1230CSW	30	6500K	3300	110	White	Non Dimmable

Line Drawing



Polar Curve



Colour



Black

White

Feature & Benefits

- Colour switchable between 3000K, 4000K & 6500K
- Supplied with 1.5 metre suspension cable & surface mount brackets
- Interconnecting connector supplied
- Can be surface mounted or suspended
- PLEASE NOTE: Product cannot be surface mounted in continuous lengths
- Emergency self test option
- 5 Year Warranty

Product Specs:

Input Frequency	50/60HZ	IP Rating	IP20
Lifetime L70 (hrs)	50000hrs	Lifetime L80 (Hours)	50000hrs
Width (mm)	59	Length (mm)	1200
Height (mm)	70	Product Type	Linears
Operating Temp. (Min) °C	-20°C	Operating Temp. (Max) °C	45°C

Compliance & Approvals:



Warranty:

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.