



Telic

Telic CCT Floodlight 20W Black Code: ATEL20/1/B

| Category | Floodlights | |
|---------------|---|--|
| Application | Commercial, Education, Healthcare, Hospitality, | |
| | Industrial, Outdoor, Residential, Retail | |
| Specification | Architectural | |



PRODUCT FEATURES

- Modern slimline LED floodlight with sleek unique design suitable for residential and commercial applications
- CCT selectable between 3000K, 4000K and 6000K
- Loop-in, loop-out junction back on the rear of the fitting
- Bracket design allows installation without removing mounting bracket

| GENERAL INFORMATION | | | |
|-------------------------|-----------------|--|--|
| Wattage | 20W | | |
| Lumens Delivered | 1700lm (4000K) | | |
| Lm/W | 901m/W (4000K) | | |
| Beam Angle | 90 | | |
| CRI | 80 | | |
| CCT | 3000/4000/6000K | | |
| Input | 220/240V | | |
| Operating Temp | -20°C - 40°C | | |
| SDCM | 6 | | |
| Energy efficiency class | E | | |
| | | | |

| • | Die-cast construction and heat sink design providing optimised thermal characteristics |
|---|--|
| | for optimum LED life and performance |

- Plug and play PIR complete with manual override facility
- Pre-installed breathable gland prevents internal moisture accumulation
- Black textured paint finish

| TECHNICAL INFORMATION | | | |
|--------------------------------|---------------------|--|--|
| Light Source | LED | | |
| Colour / Finish | Black | | |
| IP Rating | IP65 | | |
| Class Protection | 1 | | |
| Internal / External | Internal / External | | |
| Surface / Recessed / Suspended | Surface | | |
| Lumen Depreciation L70 B50 | L70 B50 60,000h | | |
| Warranty (Years) | 6 | | |
| CE Mark | Yes | | |
| Height | 225 mm | | |